


Top Loading Valves


C



TLV-300TFVBVIAL



AT1350-3



VB-050-BSP

Application

- For use in top loading fuels and other low-viscosity media

Features

- BSP threaded vacuum breaker standard
- TTMA flanges on both ends standard
- Manually operated "deadman" style with spring-loaded handle
- Optional remote handle available
- Manual or remote controlled valve mounts before the loading arm leg to allow for flow control

Materials

- Valve: aluminum
- Vacuum breaker body: brass
- Vacuum breaker housing: aluminum
- Seals: FKM

Size	Description	Part #
3"	top loading valve with vacuum breaker	TLV-300TFVBVIAL
4"		TLV-400TFVBVIAL
3"	valve remote, handle, and bracket kit	AT1350-3
4"		AT1350-4
1/2"	vacuum breaker, BSP threads	VB-050-BSP
	vacuum breaker, NPT threads	VB-050-NPT

Top Loading Diffusers/T-Deflectors



TLD-300S



400-TLTD-AL

Application

- Installed on drop leg of a top-load loading arm to distribute media evenly to help reduce splash

Features

- Diffusers distribute media evenly 360°
- T-deflectors distribute media to the sides of the tank, railcar, or tote

Size	Description	Aluminum Part #
2"	T-deflector	200-TLTD-AL
3"	360° diffuser	TLD-300S
	T-deflector	300-TLTD-AL
4"	360° diffuser	TLD-400S
	T-deflector	400-TLTD-AL