

Tectite™ by Apollo® Push to Connect Fittings

Applications

- For water, dry, clean air, or 100% glycol solutions only
- Connects copper, CPVC, and PEX pipe in any combination
- Approved for use underground and behind walls without access panels



Features

- No soldering, clamps, unions, or glue needed
- Integral tube liner for PEX installations
- Fittings can be rotated after assembly for easier installation in tight spaces
- Easy to disconnect if needed
- All Tectite by Apollo fittings are lead-free

Specification

- Pressure rating: 200 PSI at 200°F (93°C)

Approvals

- Design certified and listed to ASSE 1061/NSF 61
- Listed by IAPMO
- Meets UPC, IPC, and cUPC requirements

Straight Couplings

| Tube Size | Forged Brass Part # |
|-------------|---------------------|
| 1/2" x 1/2" | U008 |
| 3/4" x 3/4" | U016 |
| 1" x 1" | U020 |



Reducing Couplings

| Tube Size | Forged Brass Part # |
|-------------|---------------------|
| 3/4" x 1/2" | U058 |
| 1" x 3/4" | U060 |



Straight Connectors

| Tube Size | Female NPT | Forged Brass Part # |
|-----------|------------|---------------------|
| 1/2" | 1/2" | U072 |
| 3/4" | 3/4" | U088 |
| 1" | 1" | U094 |



| Tube Size | Male NPT | Forged Brass Part # |
|-----------|----------|---------------------|
| 1/2" | 1/2" | U120 |
| 3/4" | 3/4" | U134 |
| 1" | 1" | U140 |



Reducing Connectors

| Tube Size | Female NPT | Forged Brass Part # |
|-----------|------------|---------------------|
| 1/2" | 3/4" | U068 |



| Tube Size | Male NPT | Forged Brass Part # |
|-----------|----------|---------------------|
| 1/2" | 3/4" | U116 |

