

SSA - Storz x Storz Adapter

Materials

- Nitrile rubber gaskets
- Cast aluminum lock lever assembly on 4", 5" and 6"

Specification

- Working pressure: 150 PSI at 70°F (21°C)

Storz Size	Storz Size	6061-T6 Forged Aluminum Part #
1-1/2"	2"	SSA1520
	2-1/2"	SSA1525
2"	2-1/2"	SSA2025
	3"	SSA2030
	4"	SSA2540
4"	5"	SSA4050
	6"	SSA4060
5"		SSA5060



SSA30 - Storz x Storz 30° Elbow Adapters

Materials

- Nitrile rubber gaskets
- Cast aluminum lock lever assembly on 4", 5" and 6"

Specification

- Working pressure: 150 PSI at 70°F (21°C)

Storz Size	Storz Size	6061-T6 Forged Aluminum Part #
5"	5"	SSA30-550



Dixon® Storz Hydrant Conversion Adapters

Features

- Secured to hydrant by three set screws positioned around the rim
- Hydrant side: metal face to seal to gasketed face on hose
- Reflective stripe around the rim for ease of night time location

Specification

- Designed to adapt 4-1/2" NH threads found on most hydrants to Storz connection

Size	Part #
5" Storz x 4-1/2" NH (NST)	SHA5045F



Storz Fire Department Connections

Features

- Designed to work with 5" Storz universal connections
- UL approve screen helps to keep debris out of the line

Specifications

- Maximum working pressure: 250 PSI at 70°F (21°C)

Approval

- Screen is UL approved

With Screen

Storz Size	Female	Part #
5"	BSP	FDCS500BS
	NPT	FDCS500T

Without Screen

Storz Size	Female	Aluminum Part #
5"	BSP	FDC500BS
	NPT	FDC500T

