

PVC Tubing

Application

- For use with standard shank fittings in low-pressure liquid and pneumatic applications

Domestic

Application

- For non-critical hospital use such as suction and draining

Features

- Made from non-toxic ingredients conforming to FDA standards
- Phthalate, DEHP, and BPA free
- Shipped in individually boxed bundles, sold only in lengths shown below

Specification

- Maximum temperature: **175°F (79°C)**

Approvals

- Finished product meets USP class VI
- NSF-51 certified
- Reach and RoHS compliant
- Raw materials meet California Proposition 65



Size		Working Pressure PSI at 70°F (21°C)	Length	Clear PVC Part #	
O.D.	I.D.				
5/16"	3/16"	106	100'	CL0305	
3/8"	1/4"	85		CL0406	
1/2"	1/4"	141		CL0408	
7/16"	5/16"	71		CL0507	
1/2"	3/8"	70		CL0608	
5/8"	3/8"	111		CL0610	
5/8"	1/2"	52		CL0810	
3/4"	1/2"	85		CL0812	
7/8"	5/8"	71		CL1014	
1"	3/4"	61		CL1216	
1-1/4"	1"	42		CL1620	
1-3/4"	1-1/4"	71		50'	CL2028-50
2"	1-1/2"	61			CL2432-50

Imported

Feature

- Shipped in bundles wrapped with PVC film, sold only in lengths shown below

Specification

- Temperature range: **14°F to 149°F (-10°C to 65°C)**



Size		Working Pressure PSI at 72°F (22°C)	Length	Clear PVC Part #
O.D.	I.D.			
3/8"	1/4"	50	100'	ICL0406
1/2"	3/8"	35		ICL0608
5/8"	1/2"	35		ICL0810
3/4"	1/2"	50		ICL0812
1"	3/4"	35		ICL1216
1-1/4"	1"	30		ICL1620
2"	1-1/2"	15	50'	ICL2432