

DEF Automatic Shutoff Nozzle

Application

- Designed for diesel exhaust fluid applications

Materials

- Spout: stainless steel
- Wetted parts: stainless, acetal, PTFE
- Seal: FKM-A

Specification


- Maximum operating pressure: **20 PSI**
- Aluminum body double coated inside and out with PTFE baked on at **500°F (260°C)**



BSP Inlet	Spout Outlet	Approximate Flow Rate at 20 PSI (GPM)	Part #
3/4"	13/16"	18	DEFN075

High Flow Fueler 100™ Nozzles

Applications

- For fueling trucks, buses, off-road equipment, and fuel oil delivery
- These nozzles are not to be used with gravity flow tanks 

Features

- Machined grooves in the spout are designed to hold nozzle more securely in the fill pipe
- High flow, heavy duty automatic nozzle

NPT Inlet	Spout Outlet	Approximate Flow Rate at 30 PSI (GPM) ²	Approximate Flow Rate at 50 PSI (GPM) ²	Part #
1-1/4"	1-3/8"	27-30	40-42	DNOG5-NL ^{1,2}
		27-30	40-42	DNOG5 ²
1-1/2"		27-30	40-42	DNOG6 ²



¹ Without the locking handle

² Nozzle maximum pressure **50 PSI**

NPT Inlet	Spout Outlet	Approximate Flow Rate at 100 PSI (GPM) ³	Part #
1-1/4"	1-3/8"	87-90	DNOG5PL ³
1-1/2"		87-90	DNOG6PL ³

³ Nozzle maximum pressure **100 PSI**