

Turbo Nozzles



PW-AL-TPR25-30



PW-AL-TPR25-50

Features

- 20° spray angle
- Ceramic orifice

Specification

- Maximum temperature: 212°F (100°C)

Nozzle Size	Description	Orifice	Maximum Working PSI	Required Case Qty	Part #
4.0	1/4" female inlet	1.30 mm	3,700	2	PW-AL-TPR25-30
5.5 - 6.0	1/4" female inlet	1.50 mm	3,700	2	PW-AL-TPR25-50

Pressure Washer Spray Nozzles



Description	Required Case Qty	Part #
1/4" male inlet, 40° spray angle, size #40, brass	4	PW-NZ4040S
1/4" male inlet, 80° spray angle, size #40, brass	4	PW-NZ8040S
1/4" male NPT inlet, 15° spray angle, size 4, steel	4	PW-NZ1504 ¹
1/4" male NPT inlet, 25° spray angle, size 4, steel	4	PW-NZ2504 ¹
1/4" male NPT inlet, 40° spray angle, size 4, steel	4	PW-NZ4004 ¹

¹ 400-Series stainless steel parts

Anti-Fatigue Pressure Spray Gun

Sizes

- 3/8" female inlet
- 1/4" female outlet

Feature

- Anti-fatigue pressure compensating design

Specification

- Temperatures to: 320°F (160°C)



Maximum PSI	GPM	Required Case Qty	Part #
5075	12.0	4	PW-HPSPG

