


**Products Recommended for Steam Service**

**Quick Disconnect Fittings**




- Available in solid brass with stainless steel springs and locking balls
- Sizes 1/4" through 1-1/2"
- For more information see pages 498-511

**D Dry Disconnect Fittings**



- Available in stainless steel, with EPDM seals
- Sizes 3/4", 1", 1-1/2" and 2"
- For more information see pages 93-106

**GJ Boss Female Ground Joint Fittings**



- Available in plated steel and/or iron
- Sizes 1/4" through 6"
- For more information see page 162

**Boss Female Washer Seal Fittings**



- Available in plated steel and/or iron
- Sizes 3/8" through 3"
- For more information see page 165

**Boss Male Stems**



- Available in steel bar stock sizes 1/4" through 1"; iron in sizes 1-1/4" through 4"; 316 stainless steel in sizes 1/2" through 4" and brass in sizes 3/4" through 3"
- For more information see page 167

**Boss Clamps**



- 2-bolt and 4-bolt style available in plated iron in sizes 1/4" through 3"; stainless steel in sizes 1/2" through 3" and brass in sizes 1/2" through 2"
- Three-piece style are available in plated iron in sizes 3" through 6"
- For more information see pages 169 and 170

**180° Steam Gauge Siphons**



- Available in steel and red brass pipe
- 1/4" NPT schedule 40 steel, welded
- For more information see page 366

**250 PSIG Steam Ball Valves**



- Available in bronze with 316 stainless steel ball and stem
- Sizes 1/2" through 2"
- For more information see page 894



**WARNING:** Pressurized steam is an extremely dangerous commodity. Only hose, fittings, clamps, and accessory items that have been tested and approved by Dixon for use with Dixon products for steam service should ever be used. Never use an unapproved item for steam service. Always follow the manufacturer's product recommendations for pressurized steam handling.