

Hydraulic Adapters – 37° JIC

45° Male Flare x Male NPTF Elbows

Specifications

- Reference SAE 070302
- Pressure rating at 70°F (21°C)

| Male JIC 37° Flare | Male NPTF | PSI | Zinc Plated Steel Part # |
|--------------------|-----------|-------------|--------------------------|
| 7/16" – 20 | 1/8" – 27 | 4500 | 2503-4-2 |
| | 1/4" – 18 | | 2503-4-4 |
| 9/16" – 18 | 1/4" – 18 | 4000 | 2503-6-4 |
| | 3/8" – 18 | | 2503-6-6 |
| 3/4" – 16 | 1/4" – 18 | 3000 | 2503-8-4 |
| | 3/8" – 18 | | 2503-8-6 |
| | 1/2" – 14 | | 2503-8-8 |
| 7/8" – 14 | 1/2" – 14 | 2500 | 2503-10-8 |
| | 3/4" – 14 | | 2503-10-12 |
| 1-1/16" – 12 | 3/4" – 14 | 2500 | 2503-12-12 |
| 1-5/16" – 12 | 3/4" – 14 | | 2503-16-12 |
| | | 1" – 11-1/2 | 2000 |




Specifications

- Reference SAE 070401
- Pressure rating at 70°F (21°C)

Male Flare Union Tees

| Male JIC 37° Flare (3) | PSI | Zinc Plated Steel Part # |
|------------------------|------|--------------------------|
| 7/16" – 20 | 5000 | 2603-4 |
| 9/16" – 18 | | 2603-6 |
| 3/4" – 16 | 4500 | 2603-8 |
| 7/8" – 14 | 3500 | 2603-10 |
| 1-1/16" – 12 | | 2603-12 |
| 1-5/16" – 12 | 3000 | 2603-16 |



Specifications

- Reference SAE 070433
- Pressure rating at 70°F (21°C)

Male Flare x Female Swivel Tees

| Male JIC 37° Flare (2) | Female JIC 37° Swivel | PSI | Zinc Plated Steel Part # |
|------------------------|-----------------------|------|--------------------------|
| 7/16" – 20 | 7/16" – 20 | 4500 | 6600-4 |
| 9/16" – 18 | 9/16" – 18 | 4000 | 6600-6 |
| 3/4" – 16 | 3/4" – 16 | | 6600-8 |
| 1 1/16" – 12 | 1 1/16" – 12 | 3000 | 6600-12 |
| 1 5/16" – 12 | 1 5/16" – 12 | 2500 | 6600-16 |




Specifications

- Reference SAE 070432
- Pressure rating at 70°F (21°C)

Male Flare x Female Swivel Branch Tees

| Male JIC 37° Flare (2) | Female JIC 37° Swivel | PSI | Zinc Plated Steel Part # |
|------------------------|-----------------------|------|--------------------------|
| 7/16" – 20 | 7/16" – 20 | 4500 | 6602-4 |
| 9/16" – 18 | 9/16" – 18 | 4000 | 6602-6 |
| 3/4" – 16 | 3/4" – 16 | | 6602-8 |
| 7/8" – 14 | 7/8" – 14 | 3000 | 6602-10 |
| 1-1/16" – 12 | 1-1/16" – 12 | | 6602-12 |
| 1-5/16" – 12 | 1-5/16" – 12 | 2500 | 6602-16 |
| 1-5/8" – 12 | 1-5/8" – 12 | 2000 | 6602-20 |



Specifications

- Reference SAE 070425
- Pressure rating at 70°F (21°C)

Male Flare x Male NPTF Branch Tees

| Male JIC 37° Flare (2) | Male NPTF | PSI | Zinc Plated Steel Part # |
|------------------------|-------------|------|--------------------------|
| 7/16" – 20 | 1/4" – 18 | 5000 | 2601-4-4-4 |
| | 1/4" – 18 | | 2601-6-6-4 |
| 9/16" – 18 | 3/8" – 18 | 4000 | 2601-6-6-6 |
| | 1/2" – 14 | | 2601-8-8-8 |
| 3/4" – 16 | 1/2" – 14 | 3000 | 2601-10-10-8 |
| | 7/8" – 14 | | 2601-12-12-12 |
| 1-1/16" – 12 | 3/4" – 14 | 2500 | 2601-12-12-12 |
| 1-5/16" – 12 | 1" – 11-1/2 | 2000 | 2601-16-16-16 |

