

## Telescoping Lance and Belt for Pressure Gun

### Features

- 3/8" female (pipe thread) inlet
- 1/4" female (quick connect) outlet
- Length is in three sections
- 1/4" steel braided hose

### Specifications

- Maximum operating pressure: **4000 PSI**
- **7 GPM** flow rate
- Maximum temperature: **300°F (149°C)**

Length	Aluminum Part #
6' – 18'	ARTEL18A



## Swiveling Quick Couplings

### Specifications

- Working pressure: **3650 PSI**
- **7.8 GPM** flow rate
- Maximum temperature: **300°F (149°C)**

### 1/4" swiveling quick couplings

Description	Part #
1/4" female x 22 mm x 1.5 mm swivel	AL450 <sup>1</sup>

<sup>1</sup> For use with AL455F and AL456 on page 416



Description	Part #
1/4" male x 22 mm x 1.5 mm swivel	AL451 <sup>2</sup>

<sup>2</sup> For use with AL454, AL455F, and AL456 on page 416



### 3/8" swiveling quick couplings

Description	Part #
3/8" female x 22 mm x 1.5 mm swivel	AL453 <sup>1</sup>

<sup>1</sup> For use with AL455F and AL456 on page 416



Description	Part #
3/8" female inlet x 1/2" female outlet swivel	AL462 <sup>2</sup>

<sup>2</sup> For use with AL464 only on page 416

