

### Fixed Plugs

**Specifications**

- Working pressure: **3650 PSI**
- **7.8 GPM** flow rate
- Maximum temperature: **300°F (149°C)**



#### 1/4" fixed quick coupling plugs

Description	Part #
1/4" female x 22 mm x 1.5 mm male	AL454 <sup>1</sup>

<sup>1</sup> For use with AL451, AL453, and AL9 on page 415



Description	Part #
1/4" male x 22 mm x 1.5 mm male	AL455F <sup>2</sup>

<sup>2</sup> For use with AL450, AL451, and AL453 on page 415

#### 3/8" fixed quick coupling plugs



Description	Part #
3/8" female x 22 mm x 1.5 mm male	AL456 <sup>1</sup>

<sup>1</sup> For use with AL450, AL451, AL453, and AL9 on pages 413, 415



Description	Nickel Plated Brass Part #
3/8" female x 1/2" male plug	AL464 <sup>2</sup>

<sup>2</sup> For use with AL462 only on page 415

### Sewer Nozzles

**Specifications**

- Working pressure: **3625 PSI**
- Maximum temperature: **300°F (149°C)**



Size	Orifice	303 Stainless Steel Part #
3/8"	4.5 mm	SWNZ380-045
	5 mm	SWNZ380-050

### Injector Nozzles

**Features**

- Designed to inject cleaning solutions into high pressure discharge lines
- 3/8" male inlet and outlet

**Specification**

- Maximum working pressure: **4500 PSI**



AL477

Description	Orifice	Flow (GPM)	Part #
adjustable	1.8 mm	<b>2 – 8</b>	AL472
adjustable	2.1 mm	<b>3 – 8</b>	AL477
adjustable	2.3 mm	<b>4 – 8</b>	AL478

### Line Strainer

**Features**

- 3/4" female GHT inlet, 1/2" male NPT outlet
- .60 mesh cuffed filter
- 2 additional 1/4" side ports



**Specification**

- Maximum flow rate: **8 GPM**

Aluminum Part #
AR3000-A2

H