

### Y Coupler



**Specifications**

- Maximum working pressure: 100 PSI
- Maximum temperature: 100°F (38°C)

Description	Zinc with TBR Washer Part #
double male GH x female GH	500YCZ

### GHT 4-Valve Manifold

**Features**

- Swivel inlet

**Materials**

- Cast brass body, TPR handle, POM Internal valve, NBR seals

**Specifications**

- Maximum temperature: 120°F (49°C)
- Maximum operating pressure: 100 PSI



Description	Part #
3/4" female x (4) 3/4" male GH	500GH4VBK

### GHT Backflow Preventer

**Features**

- Manual drain
- Corrosion resistant
- Tamper-proof protection

**Materials**

- Lead-free brass (NSF 372) extruded stock
- Gasket: nitrile rubber
- Components: stainless steel

**Specifications**

- Maximum operating pressure: 125 PSI
- Temperature range: 33°F to 180°F (.5°C to 82°C)



Description	Part #
3/4" female x 3/4" male GH	500BFP

### Radiator Bibb

**Feature**

- 1/4" female pipe thread connection
- Fill radiators and other heat exchanger tanks; molded rubber nozzle; internal screen prevents debris from entering



Vinyl Part #
8013

### Garden Hose Gooseneck

**Feature**

- Angles hose away from hose bibb

**Specifications**

- Recommended usage: 100°F (38°C)
- Working pressure: 60 PSI



Powder-coated Zinc Part #
GHGN

H