

HTZ-Series Correct Connect®

Flush Face Female Threaded Coupler

Features

- For use with HT- or HTE-Series plugs
- Connectable with trapped pressure on HTZ half only
- ISO16028 interchange

Specifications

- Connect under pressure up to **1,500 PSI at 70°F (21°C)**
- Pressure rating **5,000 PSI at 70°F (21°C)**



Body Size	Threads	Steel Part #
1/2"	1/2" – 14 NPTF	4HTZF4
	3/4" – 14 NPTF	4HTZF6
	3/4" – 16 ORB	4HTZOF4
	7/8" – 14 ORB	4HTZOF5
	1-1/16" – 12 ORB	4HTZOF6

Flush Face ISO16028 – AG ISO7241-A Adapter

Features

- Easily adapt machinery that uses AG style quick disconnects with flat face attachments or machinery that has flat face style quick disconnects with attachments that use the AG style
- Includes Correct Connect color banding system

Interchange Data

- Agricultural Interchange, Parker®/Pioneer® 4000 Series, Faster® NS/NV-Series, Safeway® Series-S20, and Stucchi® IR-Series
- Conforms to ISO16028 interchange standard, with Eaton®/Hansen® FF, Parker FEM, Faster FFH/2FFN/2FFI, Stucchi A/FIRG, and Holmbury® HQ/A/FIMC

Specification

- Maximum working pressure: **4,000 PSI at 70°F (21°C)**



4HTAG4



4AGHT4

Industry/Competitor Interchange

Body Size	Description	Steel Part #
1/2"	ISO16028 flush face coupler x AG ISO7241-A plug	4HTAG4
	AG ISO7241-A coupler x ISO16028 flush face plug	4AGHT4

Profiles

Hansen FF, Aeroquip/Eaton FD89, Stucchi FIRG/Series 'A', Faster FFN/FFI/2FFN/2FFI, Safeway FF49-Series

