

Hydraulic Adapters – Flat Face

Male x Male NPTF 90° Elbows



Specifications

- Reference SAE 520202
- Pressure rating at 70°F (21°C)

Male Flat Face	Male NPTF	PSI	Zinc Plated Steel Part #
9/16" – 18	1/4" – 18	5000	FS2501-4-4
11/16" – 16	3/8" – 18	4000	FS2501-6-6
13/16" – 16	1/2" – 14	3000	FS2501-8-8
1-3/16" – 12	3/4" – 14	2500	FS2501-12-12
1-7/16" – 12	1" – 11-1/2	2000	FS2501-16-16

Male Union Tees

Specifications

- Reference SAE 520401
- Pressure rating at 70°F (21°C)



Male Flat Face	Male Flat Face	Male Flat Face	PSI	Zinc Plated Steel Part #
9/16" – 18	9/16" – 18	9/16" – 18	6000	FS2603-4
11/16" – 16	11/16" – 16	11/16" – 16		FS2603-6
13/16" – 16	13/16" – 16	13/16" – 16		FS2603-8
1" – 14	1" – 14	1" – 14		FS2603-10
1-3/6" – 12	1-3/16" – 12	1-3/16" – 12		FS2603-12
1-7/16" – 12	1-7/16" – 12	1-7/16" – 12		FS2603-16

Male x Female Swivel x Male Run Tees

Specifications

- Reference SAE 520432
- Pressure rating at 70°F (21°C)



Male Flat Face	Female Flat Face Swivel	Male Flat Face	PSI	Zinc Plated Steel Part #
9/16" – 18	9/16" – 18	9/16" – 18	4500	FS6602-4
11/16" – 16	11/16" – 16	11/16" – 16	4000	FS6602-6
13/16" – 16	13/16" – 16	13/16" – 16		FS6602-8
1" – 14	1" – 14	1" – 14	3000	FS6602-10
1-3/16" – 12	1-3/16" – 12	1-3/16" – 12		FS6602-12
1-7/16" – 12	1-7/16" – 12	1-7/16" – 12	2500	FS6602-16

Caps

Specifications

- Reference SAE 520112
- Pressure rating at 70°F (21°C)



Female Flat Face	PSI	Zinc Plated Steel Part #
9/16" – 18	6000	FS304C-4
11/16" – 16		FS304C-6
13/16" – 16		FS304C-8
1" – 14		FS304C-10
1-3/16" – 12		FS304C-12
1-7/16" – 12		FS304C-16

Plugs

Specifications

- Reference SAE 520109
- Pressure rating at 70°F (21°C)



Male Flat Face	PSI	Zinc Plated Steel Part #
9/16" – 18	6000	FS2408-4
11/16" – 16		FS2408-6
13/16" – 16		FS2408-8
1" – 14		FS2408-10
1-3/16" – 12		FS2408-12
1-7/16" – 12		FS2408-16

K