

## MSHA Approved Single Jacket Mine Fire Hose

Coupled with Female and Male Aluminum Rocker Lug Expansion Ring Couplings

### Features

- Outer construction: single jacket, synthetic flame resistant
- Tube construction: flame resistant lining

### Specifications

- Proof test pressure: **500 PSI** at 70°F (21°C)
- Service test pressure: **250 PSI** at 70°F (21°C)
- Working pressure: **225 PSI** at 70°F (21°C)

### Approval

- Approved by Mine Safety and Health Administration (MSHA) for all mine fire protection applications



Size	Thread	Length	Part #
1-1/2"	NST (NH)	50'	SM515W50RAF
	NPSH		SM515W50RAS

## Double Jacket Potable Water Hose – Blue

### Features

- Outer construction: double jacket, all polyester
- Tube construction: thermoplastic

### Specifications

- Proof test pressure: **600 PSI** at 70°F (21°C)
- Service test pressure: **300 PSI** at 70°F (21°C)
- Working pressure: **270 PSI** at 70°F (21°C)

### Approval

- Liner is NSF approved for potable water; fittings are not, except for temporary/emergency drinking needs only

Coupled with Female and Male, Brass or Aluminum Rocker Lug, Expansion Ring Couplings

Size	Thread	Length	Brass Expansion Ring Part #	Aluminum Expansion Ring Part #
1-1/2"	NPSH	50'	PW615B50RBS	PW615B50RAS
		100'	PW615B100RBS	PW615B100RAS
	NST (NH)	50'	PW615B50RBF	PW615B50RAF
		100'	PW615B100RBF	PW615B100RAF
2-1/2"	NPSH	50'	PW625B50RBS	PW625B50RAS
		100'	PW625B100RBS	PW625B100RAS
	NST (NH)	50'	PW625B50RBF	PW625B50RAF
		100'	PW625B100RBF	PW625B100RAF



N

## 500# All Polyester Rack Hose – UL Labeled

### Application

- For pin rack service/emergency fire fighting only. Not to be used for washdown

### Specifications



- Proof test pressure: **300 PSI** at ambient temperature 70°F (21°C)
- Service test pressure: **150 PSI** at ambient temperature 70°F (21°C)
- Working pressure: **135 PSI** at ambient temperature 70°F (21°C)

### Materials

- Outer construction: single jacket, all polyester
- Tube construction: clear thermoplastic

### Approval

- Underwriters Listed



Coupled with Female and Male Expansion Ring Couplings

Size	Coupling Type	Length	Folded Part #	Coiled Part #
1-1/2"	pin lug, brass NST (NH)	50'	R515U50PBF/F	R515U50PBF
		100'	R515U100PBF/F	R515U100PBF
	rocker lug, aluminum NST (NH)	50'	R515U50RAF/F	R515U50RAF
		100'	R515U100RAF/F	---