

### Nitrile Washdown Hose

**Application**

- Ideal for industrial, agricultural, and construction washdown and discharge applications, not for fire fighting



**Feature**

- Resistant to weather and abrasion

**Uncoupled**



Size	Color	Bowl	Length	Working Pressure (PSI)	Part #	
1"	black	1-1/4"	50'	200	WDH10BK50UC	
			100'		WDH10BK100UC	
1-1/2"	black	1-13/16"	50'		WDH15BK50UC	
			100'		WDH15BK100UC	
2"	black	2-5/16"	50'		WDH20BK50UC	
			100'		WDH20BK100UC	
2-1/2"	black	2-13/16"	50'		WDH25BK50UC	
			100'		WDH25BK100UC	
3"	black	3-3/8"	50'		150	WDH30BK50UC
			100'			WDH30BK100UC
4"	black	4-3/8"	50'			WDH40BK50UC
			100'			WDH40BK100UC
6"	black	6-3/8"	50'			WDH60BK50UC
			100'			WDH60BK100UC



female L/H x male R/L

### Dixon® PVC Flexible Suction Hose

**Couplings with PVC Flexible Suction Hose**



storz x storz



cam & groove x cam & groove

Size	Length	Thread	Female L/H x Male Part #	Female R/L x Male Part #	Storz x Storz Part #	Cam & Groove x Cam & Groove Part #
2-1/2"	10'	NST	FSH25-10LAF	FSH25-10RAF	FSH25-10STZ	---
3"			FSH30-10LAF	FSH30-10RAF	---	FSH30-10GAX
4"			FSH40-10LAF	FSH40-10RAF	FSH40-10STZ	FSH40-10GAX
4-1/2"			FSH45-10LAF	FSH45-10RAF	---	---
5"			FSH50-10LAF	FSH50-10RAF	---	---
6"			FSH60-10LAF	FSH60-10RAF	---	FSH60-10GAX

NOTE: Additional lengths and configurations are available; contact Dixon.

