

## 2-Piece Domestic Stainless Steel Ball Valves

**Feature**


- Blow-out proof stem

**Materials**

- 316 stainless steel ball and stem
- RPTFE seal
- Vinyl handle cover

**Specifications**

- Temperature range: **-40°F to 400°F**  
(-40°C to 204°C)
- Pressure rating: **1,000 PSI CWP**
- Pressure rating: **150 PSI** saturated steam
- Vacuum service to 29 inches Hg



Female NPT	Port	316 Stainless Steel Part #
1/4"	full	DSBV25
3/8"		DSBV38
1/2"		DSBV50
3/4"		DSBV75
1"		DSBV100
1-1/4"		DSBV125
1-1/2"		DSBV150
2"		DSBV200

## Stainless Steel Ball Valves Full Port

**Applications**

- For use with water, oil, and gas

**Feature**

- Blow-out proof stem design

**Materials**

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket, and thrust washer

**Specifications**

- Temperature range: **-20°F to 428°F** (-29°C to 220°C) as long as the valve is run fully open/closed
- Pressure rating: rated to **1000 PSI WOG** (CWP)  
**100 PSI** saturated steam



Female NPT	Port	316 Stainless Steel Part #
1/4"	full	SSBV25
3/8"		SSBV38
1/2"		SSBV50
3/4"		SSBV75
1"		SSBV100
1-1/4"		SSBV125
1-1/2"		SSBV150
2"		SSBV200
2-1/2"		SSBV250
3"		SSBV300

NOTE: For all ball valve replacement handles please contact Dixon.



**WARNING:** Misuse of these products can cause serious injury or even death.



**WARNING:** Pressurized steam is an extremely dangerous commodity. Only hose, fittings, clamps, and accessory items that have been approved by Dixon for use with Dixon products for steam service should ever be used. Never use an unapproved item for steam service. Always follow the manufacturer's product recommendations for pressurized steam handling.



**WARNING:** For safety reasons, due to differences in dimensions and tolerances, do not interchange other manufacturer's products with Dixon products.