

Full Port Ball Valves with Locking Handle

Applications

- For use with water, oil, and gas

Features


- Lockable
- Blow-out proof stem design
- Not recommended as a throttling valve

Materials

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket and thrust washer
- Plastic cover on handle

Specifications

- Temperature range: -20°F to 428°F (-29°C to 220°C)
- Pressure rating: rated to **1000 PSI WOG** (CWP); **100 PSI** saturated steam



Female NPT	Port	316 Stainless Steel Part #
1/4"	full	SSLBV25
3/8"		SSLBV38
1/2"		SSLBV50
3/4"		SSLBV75
1"		SSLBV100
1-1/4"		SSLBV125
1-1/2"		SSLBV150
2"		SSLBV200
2-1/2"		SSLBV250
3"		SSLBV300

Reduced Port Ball Valves with Locking Handle

Applications

- For use with water, oil, and gas

Features


- Lockable
- Blow-out proof stem design
- Not recommended as a throttling valve

Materials

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket, and thrust washer
- Plastic cover on handle

Specifications

- Temperature range: -20°F to 428°F (-29°C to 220°C)
- Pressure rating: **1000 PSI WOG**; **100 PSI** saturated steam



Female NPT	Port	316 Stainless Steel Part #
1/4"	reduced	SSLBV25SP
3/8"		SSLBV38SP
1/2"		SSLBV50SP
3/4"		SSLBV75SP
1"		SSLBV100SP
1-1/4"		SSLBV125SP
1-1/2"		SSLBV150SP
2"		SSLBV200SP

3-Piece Full Port Stainless Steel Ball Valves

Applications

- For use with water, oil, and gas

Materials

- Stainless steel body, ball, stem, handle, and nut
- PTFE seal

Feature

- Anti-blowout, one piece bottom entry stem
- Statically grounded ball, stem, and body

Specification

- Pressure rating: **250 PSIG** saturated steam
- UL listed



Female NPT	Port	Stainless Steel Part #
1/2"	full	SS3BV50
3/4"		SS3BV75
1"		SS3BV100
1-1/4"		SS3BV125
1-1/2"		SS3BV150
2"		SS3BV200

NOTE: For all ball valve replacement handles please contact Dixon.

0

