

High Pressure Full-Bore 3-Way Ball Valves

Features

- Rugged construction
- L flow pattern

Materials

- Clear zinc carbon steel
- Nitrile rubber O-ring
- Nickel plated ball

Specification

- Temperature range: -20°F to 215°F (-29°C to 102°C)



Female NPT	PSI	Carbon Steel Part #
1/2"	5145	HPBV12-3WAYZPL
3/4"		HPBV34-3WAYZPL
1"		HPBV10-3WAYZPL

High Pressure Clear Zinc Ball Valves

Feature

- Full port, sizes 1/4 to 1", Reduced port, sizes 1-1/4 to 1-1/2"

Specification

- Temperature range: -20°F to 215°F (-29°C to 102°C)

Materials

- Nitrile rubber O-rings
- POM (Polyacetal) ball seats

Approval

- RoHS compliant



Female NPT	PSI	Carbon Steel		PSI
		Part #	SAE Part #	
1/4"	7350	HPBV25ZPL	HPBV25SAEZPL	7350
3/8"		HPBV38ZPL	HPBV38SAEZPL	
1/2"		HPBV12ZPL	HPBV12SAEZPL	
3/4"	6000	HPBV34ZPL	HPBV34SAEZPL	6000
1"		HPBV10ZPL	HPBV10SAEZPL	
1-1/4"		HPBV125ZPL	HPBV125SAEZPL	
1-1/2"		HPBV150ZPL	HPBV150SAEZPL	
2"		HPBV200ZPL	HPBV200SAEZPL	

High Pressure Full-Bore Ball Valves

Features

- Blow-out proof stem
- Rugged construction
- Full port, sizes 1/4 to 1"

Materials

- FKM/FPM seals
- POM (Polyacetal) ball seats
- 316 stainless steel

Specification

- Temperature range: -20°F to 215°F (-29°C to 101.6°C)



Female NPT	PSI	316 Stainless Steel Part #
1/4"	5880	HPBV25SS
3/8"		HPBV38SS
1/2"		HPBV12SS
3/4"	5145	HPBV34SS
1"		HPBV10SS