

Scope of Registration

Dixon Group Canada Limited – Boss Fittings

Design Code: ASME B31.3

Design Temperature: 450 °F

Design Pressure: 600 Psi



Product No.	Description	Material
GBC	Female spud	ASTM A108
GCC	Female spud	ASTM A108
GB3	Female spud	ASTM A108
GB8	Female spud	ASTM A108
GB13	Female spud	ASTM A108
GB18	Female spud	32510 ASTM A47; ASTM A536
GB23	Female spud	32510 ASTM A47; ASTM A536
GB28	Female spud	32510 ASTM A47; ASTM A536
GB33	Female spud	32510 ASTM A47; ASTM A536
GB38	Female spud	32510 ASTM A47; ASTM A536
GB48	Female spud	32510 ASTM A47
GB68	Female spud	32510 ASTM A47
GMC	Male spud	ASTM A53; ASTM A108
GM3	Male spud	ASTM A108
GM8	Male spud	ASTM A108
GM13	Male spud	ASTM A108
GM18	Male spud	32510 ASTM A47; ASTM A536
GM23	Male spud	32510 ASTM A47; ASTM A536
GM28	Male spud	32510 ASTM A47; ASTM A536
GM33	Male spud	32510 ASTM A47
GM38	Male spud	32510 ASTM A47; ASTM A536
GDB3	Double spud	ASTM A108
GDB13	Double spud	ASTM A108
GDB23	Double spud	32510 ASTM A47; ASTM A536
GDB28	Double spud	32510 ASTM A47; ASTM A536
GDB33	Double spud	32510 ASTM A47
GDB38	Double spud	32510 ASTM A47
GMAS6	Male NPT adapters	ASTM A108; ASTM A513; 32510 ASTM A47; ASTM A536
GMAS11	Male NPT adapters	ASTM A108; ASTM A513; 32510 ASTM A47; ASTM A536
GMAS16	Male NPT adapters	ASTM A108; 32510 ASTM A47; ASTM A536
GMAS21	Male NPT adapters	ASTM A108; ASTM A513; 32510 ASTM A47; ASTM A536
GMAS26	Male NPT adapters	ASTM A519; ASTM A108; ASTM A513; 32510 ASTM A47; ASTM A536
GFAS6	Female NPT adapters	ASTM A108; 32510 ASTM A47; ASTM A536
GFAS11	Female NPT adapters	ASTM A108; 32510 ASTM A47; ASTM A536
GFAS16	Female NPT adapters	ASTM A108; 32510 ASTM A47; ASTM A536
GFAS21	Female NPT adapters	ASTM A108; ASTM A513; 32510 ASTM A47; ASTM A536
GFAS26	Female NPT adapters	ASTM A519; ASTM A108; ASTM A513; 32510 ASTM A47; ASTM A536